



Figure similar

SIMATIC S7-300, Analog input SM 331, isolated, 8 AI; +/-5/10V, 1-5 V, +/-20 mA, 0/4 to 20 mA, 16 bit, Single rooting (60 V COM.), 4-channel operation: 10 ms, 8-channel operation: 23-95ms, 1x 40-pole

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	200 mA
from backplane bus 5 V DC, max.	100 mA
Power loss	
Power loss, typ.	3 W
Analog inputs	
Number of analog inputs	8
permissible input voltage for voltage input (destruction limit), max.	75 V; 35 V continuous, 75 V for max. 1 s (mark to space ratio 1:20)
permissible input current for current input (destruction limit), max.	40 mA
Input ranges	
• Voltage	Yes
• Current	Yes
• Thermocouple	No
• Resistance thermometer	No
• Resistance	No
Input ranges (rated values), voltages	
• 0 to +10 V	No
• 1 V to 5 V	Yes
— Input resistance (1 V to 5 V)	10 MΩ
• 1 V to 10 V	No
• -1 V to +1 V	No
• -10 V to +10 V	Yes
— Input resistance (-10 V to +10 V)	10 MΩ
• -2.5 V to +2.5 V	No
• -250 mV to +250 mV	No
• -5 V to +5 V	Yes
— Input resistance (-5 V to +5 V)	10 MΩ
• -50 mV to +50 mV	No
• -500 mV to +500 mV	No
• -80 mV to +80 mV	No
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	250 Ω
• -10 mA to +10 mA	No

<ul style="list-style-type: none"> • -20 mA to +20 mA <ul style="list-style-type: none"> — Input resistance (-20 mA to +20 mA) • -3.2 mA to +3.2 mA • 4 mA to 20 mA <ul style="list-style-type: none"> — Input resistance (4 mA to 20 mA) 	<p>Yes</p> <p>250 Ω</p> <p>No</p> <p>Yes</p> <p>250 Ω</p>
Input ranges (rated values), thermocouples	
<ul style="list-style-type: none"> • Type B • Type C • Type E • Type J • Type K • Type L • Type N • Type R • Type S • Type T • Type U • Type TXK/TXK(L) to GOST 	<p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p>
Input ranges (rated values), resistance thermometer	
<ul style="list-style-type: none"> • Cu 10 • Ni 100 • Ni 1000 • LG-Ni 1000 • Ni 120 • Ni 200 • Ni 500 • Pt 100 • Pt 1000 • Pt 200 • Pt 500 	<p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p>
Input ranges (rated values), resistors	
<ul style="list-style-type: none"> • 0 to 150 ohms • 0 to 300 ohms • 0 to 600 ohms • 0 to 6000 ohms 	<p>No</p> <p>No</p> <p>No</p> <p>No</p>
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	<p>200 m</p>
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> • Resolution with overrange (bit including sign), max. • Integration time, parameterizable • Basic conversion time (ms) • Interference voltage suppression for interference frequency f1 in Hz 	<p>16 bit; Unipolar: 15/15/15/15 bit; bipolar: 15 bit + sign/15 bit + sign/15 bit + sign/15 bit + sign</p> <p>Yes; 23 / 72 / 83 / 95 ms</p> <p>10 ms (4-channel mode); 95/83/72/23 ms (8-channel mode)</p> <p>400 / 60 / 50 Hz, combinations of 400, 60, 50 Hz</p>
Encoder	
Connection of signal encoders	
<ul style="list-style-type: none"> • for voltage measurement • for current measurement as 2-wire transducer • for current measurement as 4-wire transducer 	<p>Yes</p> <p>Yes; with external transmitter, current supply; possible with separate supply for transmitter</p> <p>Yes</p>
Errors/accuracies	
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> • Voltage, relative to input range, (+/-) • Current, relative to input range, (+/-) 	<p>0.1 %</p> <p>0.1 %</p>
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> • Voltage, relative to input range, (+/-) • Current, relative to input range, (+/-) 	<p>0.05 %</p> <p>0.05 %</p>
Interrupts/diagnostics/status information	
<ul style="list-style-type: none"> • Diagnostics function 	<p>Yes; Parameterizable</p>
Alarms	

<ul style="list-style-type: none"> • Diagnostic alarm • Limit value alarm • Hardware interrupt 	<p>Yes; Parameterizable</p> <p>Yes; Parameterizable all channels (end of cycle interrupt is also supported across modules)</p> <p>Yes; Parameterizable, channels 0 to 7 (on exceeding limit value), at end of cycle</p>
Diagnoses	
<ul style="list-style-type: none"> • Diagnostic information readable 	Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> • Group error SF (red) 	Yes
Potential separation	
Potential separation analog inputs	
<ul style="list-style-type: none"> • between the channels • between the channels, in groups of • between the channels and backplane bus • between the channels and the power supply of the electronics 	<p>Yes</p> <p>2</p> <p>Yes</p> <p>Yes</p>
Isolation	
Isolation tested with	500 V AC
connection method	
required front connector	40-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	117 mm
Weights	
Weight, approx.	272 g

last modified: 8/16/2023 