



SIMATIC S7-400H, CPU 414-5H, central processing unit for S7-400H and S7-400F/FH, 5 interfaces: 1x MPI/DP, 1x DP, 1x PN and 2 for sync modules, 4 MB memory (2 MB data/2 MB program),

General information	
Product type designation	CPU 414-5H PN/DP
HW functional status	1
Firmware version	V6.0
Product function	
• Isochronous mode	No
Engineering with	
• Programming package	As of STEP 7 V5.5 SP2 with HF1
CiR - Configuration in RUN	
CiR synchronization time, basic load	100 ms
CiR synchronization time, time per I/O byte	0 µs
Supply voltage	
Rated value (DC)	Power supply via system power supply
Input current	
from backplane bus 5 V DC, typ.	1.6 A
from backplane bus 5 V DC, max.	1.9 A
from backplane bus 24 V DC, max.	150 mA; 150 mA per DP interface
from interface 5 V DC, max.	90 mA; At each DP interface
Power loss	
Power loss, typ.	7.5 W
Memory	
Type of memory	other
Work memory	
• integrated	4 Mbyte
• integrated (for program)	2 Mbyte
• integrated (for data)	2 Mbyte
• expandable	No
Load memory	
• expandable FEPR0M	Yes; with Memory Card (FLASH)
• expandable FEPR0M, max.	64 Mbyte
• integrated RAM, max.	512 kbyte
• expandable RAM	Yes
• expandable RAM, max.	64 Mbyte
Backup	
• present	Yes
• with battery	Yes; all data
• without battery	No
Battery	
Backup battery	
• backup current / of backup battery / typical	180 µA; Valid up to 40°C

- backup current / of backup battery / maximum
- buffer time / of backup battery / maximum
- Feeding of external backup voltage to CPU

1 000 µA

Dealt with in the module data manual with the secondary conditions and the factors of influence

5 V DC to 15 V DC

CPU processing times

for bit operations, typ.	18.75 ns
for word operations, typ.	18.75 ns
for fixed point arithmetic, typ.	18.75 ns
for floating point arithmetic, typ.	37.5 ns

CPU-blocks

DB	
• Number, max.	6 000; Number range: 1 to 16000
• Size, max.	64 kbyte

FB	
• Number, max.	3 000; Number range: 0 to 7999
• Size, max.	64 kbyte

FC	
• Number, max.	3 000; Number range: 0 to 7999
• Size, max.	64 kbyte

OB	
• Number, max.	see instruction list
• Size, max.	64 kbyte
• Number of free cycle OBs	1; OB 1
• Number of time alarm OBs	4; OB 10-13
• Number of delay alarm OBs	4; OB 20-23
• Number of cyclic interrupt OBs	4; OB 32-35
• Number of process alarm OBs	4; OB 40-43
• Number of DPV1 alarm OBs	3; OB 55-57
• Number of startup OBs	2; OB 100, 102
• Number of asynchronous error OBs	9; OB 80-88
• Number of synchronous error OBs	2; OB 121, 122

Nesting depth	
• per priority class	24
• additional within an error OB	1

Counters, timers and their retentivity

S7 counter	
• Number	2 048
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	2 047
— preset	Z 0 to Z 7

Counting range	
— lower limit	0
— upper limit	999

IEC counter	
• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)

S7 times	
• Number	2 048
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	2 047
— preset	No times retentive

Time range	
— lower limit	10 ms
— upper limit	9 990 s

IEC timer	
• present	Yes

• Type	SFB
• Number	Unlimited (limited only by RAM capacity)
Data areas and their retentivity	
Retentive data area (incl. timers, counters, flags), max.	Total working and load memory (with backup battery)
Flag	
• Size, max.	8 192 byte
• Retentivity available	Yes
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; in 1 memory byte
Local data	
• adjustable, max.	16 kbyte
• preset	8 kbyte
Address area	
I/O address area	
• Inputs	8 kbyte
• Outputs	8 kbyte
Process image	
• Inputs, adjustable	8 kbyte
• Outputs, adjustable	8 kbyte
• Inputs, default	256 byte
• Outputs, default	256 byte
• consistent data, max.	244 byte
• Access to consistent data in process image	Yes
Subprocess images	
• Number of subprocess images, max.	15
Digital channels	
• Inputs	65 536
— of which central	65 536
• Outputs	65 536
— of which central	65 536
Analog channels	
• Inputs	4 096
— of which central	4 096
• Outputs	4 096
— of which central	4 096
Hardware configuration	
Number of expansion units, max.	21
connectable OPs	63
Multicomputing	No
Interface modules	
• Number of connectable IMs (total), max.	6
• Number of connectable IM 460s, max.	6
• Number of connectable IM 463s, max.	4; Single mode only
Number of DP masters	
• integrated	2
• via CP	10; CP 443-5 Extended
• Mixed mode IM + CP permitted	No
• via interface module	0
Number of IO Controllers	
• integrated	1
• via CP	0
Number of operable FMs and CPs (recommended)	
• FM	See manual Automation System S7-400H fault-tolerant systems. Limited by number of slots and number of connections
• CP, PtP	See manual Automation System S7-400H fault-tolerant systems. Limited by number of slots and number of connections
• PROFIBUS and Ethernet CPs	14; Of which max. 10 CP as DP master
Slots	
• required slots	2
Time of day	
Clock	

• Hardware clock (real-time)	Yes
• retentive and synchronizable	Yes
• Resolution	1 ms
• Deviation per day (buffered), max.	1.7 s; Power off
• Deviation per day (unbuffered), max.	8.6 s; Power on
Operating hours counter	
• Number	16
• Number/Number range	0 to 15
• Range of values	SFCs 2, 3 and 4: 0 to 32767 hours SFC 101: 0 to 2 ³¹ - 1 hours
• Granularity	1 h
• retentive	Yes
Clock synchronization	
• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes
• to DP, master	Yes
• to DP, slave	Yes
• in AS, master	Yes
• in AS, slave	Yes
• on Ethernet via NTP	Yes; As client
Time difference in system when synchronizing via	
• Ethernet, max.	10 ms; Via NTP
• MPI, max.	200 ms
Interfaces	
Number of RS 485 interfaces	2
Number of other interfaces	2; Fiber-optic interface
Optical interface	No
1. Interface	
Interface type	MPI/PROFIBUS DP
Isolated	Yes
Interface types	
• RS 485	Yes
• Output current of the interface, max.	150 mA
Protocols	
• MPI	Yes
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	No
MPI	
• Number of connections	32; If a diagnostics repeater is used on the line, the number of connection resources on the line is reduced by 1
• Transmission rate, max.	12 Mbit/s
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
PROFIBUS DP master	
• Number of connections, max.	16; If a diagnostics repeater is used on the line, the number of connection resources on the line is reduced by 1
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	32
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	Yes

— S7 communication, as server	Yes
— Equidistance	No
— Isochronous mode	No
— SYNC/FREEZE	No
— Activation/deactivation of DP slaves	No
— Direct data exchange (slave-to-slave communication)	No
— DPV1	Yes
Address area	
— Inputs, max.	2 kbyte
— Outputs, max.	2 kbyte
User data per DP slave	
— User data per DP slave, max.	244 byte
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
PROFIBUS DP slave	
• Number of connections	No configuration of CPU as DP slave
2. Interface	
Interface type	PROFINET
Isolated	Yes
automatic detection of transmission rate	Yes; Autosensing
Autonegotiation	Yes
Autocrossing	Yes
Change of IP address at runtime, supported	No
Number of connection resources	64
Interface types	
• RJ 45 (Ethernet)	Yes
• Number of ports	2
• integrated switch	Yes
Protocols	
• PROFINET IO Controller	Yes
• PROFINET IO Device	No
• PROFINET CBA	No
• PROFIBUS DP master	No
• PROFIBUS DP slave	No
• Open IE communication	Yes
• Web server	No
• Point-to-point connection	No
• Media redundancy	Yes
PROFINET IO Controller	
• Transmission rate, max.	100 Mbit/s
Services	
— PG/OP communication	Yes
— S7 communication	Yes
— Isochronous mode	No
— Shared device	Yes; Single mode only
— Prioritized startup	No
— Number of connectable IO Devices, max.	256; In redundant mode via both interfaces
— Number of connectable IO Devices for RT, max.	256
— of which in line, max.	256
— Activation/deactivation of IO Devices	No
— IO Devices changing during operation (partner ports), supported	No
— Device replacement without swap medium	Yes
— Send cycles	250 μ s, 500 μ s, 1 ms, 2 ms, 4 ms
— Updating time	250 μ s to 512 ms, minimum value depends on the number of configured user data and the configured single or redundant mode
Address area	
— Inputs, max.	8 kbyte
— Outputs, max.	8 kbyte

— User data consistency, max.	1 024 byte
Open IE communication	
• Number of connections, max.	62
• Local port numbers used at the system end	0, 20, 21, 25, 102, 135, 161, 34962, 34963, 34964, 65532, 65533, 65534, 65535
• Keep-alive function, supported	Yes
3. Interface	
Interface type	PROFIBUS DP
Number of connection resources	16
Interface types	
• RS 485	Yes
• Output current of the interface, max.	150 mA
Protocols	
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	No
PROFIBUS DP master	
• Number of connections, max.	16
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	96
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
— Equidistance	No
— Isochronous mode	No
— SYNC/FREEZE	No
— Activation/deactivation of DP slaves	No
— Direct data exchange (slave-to-slave communication)	No
— DPV0	Yes
— DPV1	Yes
Address area	
— Inputs, max.	6 kbyte
— Outputs, max.	6 kbyte
User data per DP slave	
— User data per DP slave, max.	244 byte
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
4. Interface	
Interface type	Pluggable synchronization submodule (FO)
Plug-in interface modules	Synchronization modules 6ES7960-1AA06-0XA0 or 6ES7960-1AB06-0XA0
5. Interface	
Interface type	Pluggable synchronization submodule (FO)
Plug-in interface modules	Synchronization modules 6ES7960-1AA06-0XA0 or 6ES7960-1AB06-0XA0
Protocols	
Redundancy mode	
Media redundancy	
— Switchover time on line break, typ.	200 ms
— Number of stations in the ring, max.	50
SIMATIC communication	
• S7 routing	Yes
Open IE communication	
• TCP/IP	Yes; via integrated PROFINET interface and loadable FBs
— Number of connections, max.	62
— Data length, max.	32 kbyte

<ul style="list-style-type: none"> — several passive connections per port, supported 	Yes
<ul style="list-style-type: none"> ● ISO-on-TCP (RFC1006) <ul style="list-style-type: none"> — Number of connections, max. — Data length, max. 	Yes; Via integrated PROFINET interface or CP 443-1 and loadable FBs 62 32 kbyte; 1 452 bytes via CP 443-1 Adv.
<ul style="list-style-type: none"> ● UDP <ul style="list-style-type: none"> — Number of connections, max. — Data length, max. 	Yes; via integrated PROFINET interface and loadable FBs 62 1 472 byte
Web server	
<ul style="list-style-type: none"> ● supported 	No
Isochronous mode	
Equidistance	No
communication functions / header	
PG/OP communication <ul style="list-style-type: none"> ● Number of connectable OPs without message processing ● Number of connectable OPs with message processing 	Yes 63 63; When using Alarm_S/SQ and Alarm_D/DQ
Data record routing	Yes
Global data communication	
<ul style="list-style-type: none"> ● supported 	No
S7 basic communication	
<ul style="list-style-type: none"> ● communication function / S7 basic communication 	No
S7 communication	
<ul style="list-style-type: none"> ● supported ● as server ● as client ● User data per job, max. ● User data per job (of which consistent), max. 	Yes Yes Yes 64 kbyte 462 byte; 1 variable
S5 compatible communication	
<ul style="list-style-type: none"> ● supported ● User data per job, max. ● User data per job (of which consistent), max. ● Number of simultaneous AG-SEND/AG-RECV orders per CPU, max. 	Yes; (via CP max. 10 and FC AG_SEND and FC AG_RECV) 8 kbyte 240 byte 64/64
Standard communication (FMS)	
<ul style="list-style-type: none"> ● supported 	Yes; Via CP and loadable FB
Number of connections	
<ul style="list-style-type: none"> ● overall ● usable for PG communication <ul style="list-style-type: none"> — reserved for PG communication — adjustable for PG communication, max. ● usable for OP communication <ul style="list-style-type: none"> — reserved for OP communication — adjustable for OP communication, max. ● usable for S7 basic communication <ul style="list-style-type: none"> — reserved for S7 basic communication — adjustable for S7 basic communication, max. ● usable for S7 communication <ul style="list-style-type: none"> — reserved for S7 communication — adjustable for S7 communication, max. ● usable for routing <ul style="list-style-type: none"> — reserved for routing — adjustable for routing, max. 	64 1 0 1 0 0 0 0 0 0
S7 message functions	
Number of login stations for message functions, max.	63; Max. 63 with Alarm_S/SQ and Alarm_D/DQ (OPs); max. 8 with Alarm, Alarm_8, Alarm_8P, Notify and Notify_8 (e.g. WinCC)
Symbol-related messages	No
SCAN procedure	No
Program alarms	Yes
Process diagnostic messages	Yes
simultaneously active Alarm-S blocks, max.	400; Simultaneously active alarm_S/SQ blocks or alarm_D/DQ blocks
Alarm 8-blocks <ul style="list-style-type: none"> ● Number of instances for alarm 8 and S7 communication 	Yes 2 500

blocks, max.	
• preset, max.	900
Process control messages	Yes
Number of archives that can log on simultaneously (SFB 37 AR_SEND)	16
Test commissioning functions	
Status block	Yes
Single step	Yes
Number of breakpoints	16
Status/control	
• Status/control variable	Yes; Up to 16 variable tables
• Variables	Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters
• Number of variables, max.	70
Forcing	
• Forcing	Yes
• Forcing, variables	Inputs/outputs, bit memories, distributed I/Os
• Number of variables, max.	256
Diagnostic buffer	
• present	Yes
• Number of entries, max.	3 200
— adjustable	Yes
— preset	120
Service data	
• can be read out	Yes
EMC	
Emission of radio interference acc. to EN 55 011	
• Limit class A, for use in industrial areas	Yes
• Limit class B, for use in residential areas	No
configuration / header	
Configuration software	
• STEP 7	Yes
configuration / programming / header	
• Command set	see instruction list
• Nesting levels	7
• Access to consistent data in process image	Yes
• System functions (SFC)	see instruction list
• System function blocks (SFB)	see instruction list
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— GRAPH	Yes
— HiGraph®	Yes
configuration / programming / number of simultaneously active SFC / header	
— RD_REC	8
— WR_REC	8
— WR_PARM	8
— PARM_MOD	1
— WR_DPARM	2
— DPNRM_DG	8
— RDSYSST	8
— DP_TOPOL	1
configuration / programming / number of simultaneously active SFB / header	
— RDREC	8
— WRREC	8
Know-how protection	
• User program protection/password protection	Yes
• Block encryption	Yes; With S7 block Privacy
Dimensions	

Width	50 mm
Height	290 mm
Depth	219 mm
Weights	
Weight, approx.	995 g

last modified: 9/7/2023 