



SIMATIC S7-400, digital input SM 421, isolated 16 DI; UC 24 - 60 V, alarm, diagnostics

Input current	
from backplane bus 5 V DC, max.	150 mA
Power loss	
Power loss, typ.	8 W; 3.5 W (24 V DC); 6.5 W (48 V DC); 8.0 W (60 V DC)
Digital inputs	
Number of digital inputs	16
Number of simultaneously controllable inputs	
• Number of simultaneously controllable inputs	16
Input voltage	
• Type of input voltage	AC/DC
• Rated value (UC)	24 V; 24 V UC to 60 V UC (47 ... 63 Hz)
• for signal "0"	-6 to +6 V DC/ 0 to 5 V AC
• for signal "1"	15 to 72 V DC; -15 to -72 V DC; 15 to 60 V AC
Input current	
• for signal "1", typ.	4 mA; 4 to 10 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes
— Rated value	0.5 ms; 0.5 / 3 / 10 / 20 ms
Encoder connection	
• Fixed current limitation for wire-break monitoring, min.	18 kΩ; 18 kohms: Rated voltage 24 V (15 to 35 V); 39 kohms: Rated voltage 48 V (30 to 60 V)
• Fixed current limitation for wire-break monitoring, max.	56 kΩ; Rated voltage 60 V (50 to 72 V)
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m; 600 m: 3, 10, 20 ms; 100 m: 0,5 ms
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	0.5 mA; 0.5 to 2 mA
Interrupts/diagnostics/status information	
Diagnostics function	Yes; Parameterizable
Alarms	
• Diagnostic alarm	Yes; Parameterizable
• Hardware interrupt	Yes; Parameterizable
Diagnoses	
• Diagnostic information readable	Yes; possible
• Wire-break	Yes; I > 0.7 mA
Diagnostics indication LED	
• Status indicator digital input (green)	Yes

• Channel fault indicator F (red)	No
<b>Potential separation</b>	
Potential separation digital inputs	
• between the channels	Yes
• between the channels, in groups of	1
• between the channels and backplane bus	Yes
<b>Isolation</b>	
Isolation tested with	1 500 V AC
<b>Dimensions</b>	
Width	25 mm
Height	290 mm
Depth	210 mm
<b>Weights</b>	
Weight, approx.	600 g
<b>last modified:</b>	8/30/2023 