



Figure similar

SIPLUS S7-1200 CM 1243-2 based on 3RK7243-2AA30-0XB0 with conformal coating, -25...+70 °C, S7-1200, CM 1243-2 communications module AS-Interface master according to AS-i specification V3.0

General technical data		
product designation		SIPLUS AS-Interface master
product type designation		CM 1243-2
protection class IP		IP20
type of electrical connection of the AS-Interface		Screw-type connection
type of voltage supply		via backplane bus
consumed current		
<ul style="list-style-type: none"> from profile conductors of the AS-Interface <ul style="list-style-type: none"> — at 30 V maximum 	mA	100
<ul style="list-style-type: none"> from backplane bus maximum 	mA	250
power loss [W]	W	2.9
insulation voltage rated value	V	500
product feature redundancy capability		No
product function suitable for AS-i Power24V		Yes
<ul style="list-style-type: none"> note 		All product versions
display version		
<ul style="list-style-type: none"> as status display by LED 		AS-i, PF, CM, CER, DIAG
type of configuration of the AS-Interface		With STEP7, command interface
Communication/ Protocol		
version of the AS-Interface specification		V 3.0
AS-Interface master profile is supported		M4 (in acc. with AS-interface specification V 3.0)
type of data transmission		S7-1200 backplane bus
number of units per CPU maximum		3
number of units per CPU maximum note		Max. 3 communication modules in total (CM /CP)
number of interfaces		
<ul style="list-style-type: none"> as AS-Interface 		1
<ul style="list-style-type: none"> according to USB 		0
protocol is supported		
<ul style="list-style-type: none"> TCP/IP 		No
Inputs/ Outputs		
number of inputs for AS-Interface maximum		496
number of outputs for AS-Interface maximum		496
number of AS-i slaves per AS-Interface maximum		62
access to digital I/O data		via process image/peripheral addresses
access to analog I/O data		via process diagram/peripheral addresses and data record transfer
Mechanical data		
fastening method		snap-on fastening on 35 mm DIN rail
module format		S7-1200 design

Ambient conditions

ambient temperature		
• if installed on horizontal mounting rail during operation	°C	0 ... 55
• if installed on vertical mounting rail during operation	°C	-25 ... +70
installation altitude at height above sea level maximum	m	2 000

Safety related data

explosion protection marking for intrinsic safety of related equipment		
• EEx ia		No
• EEx ib		No
explosion protection category for gas		none
explosion protection category for dust		none

Certificates/ approvals

General Product Approval	For use in hazardous locations
--------------------------	--------------------------------

[Miscellaneous](#)



[Manufacturer Declaration](#)



Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=6AG1243-2AA30-7XB0>

Cax online generator

<http://support.automation.siemens.com/WWW/CAXorder/default.aspx?lang=en&mlfb=6AG1243-2AA30-7XB0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/6AG1243-2AA30-7XB0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=6AG1243-2AA30-7XB0&lang=en

last modified:

5/13/2024