



Figure similar

SIPLUS NET CSM 1277 based on 6GK7277-1AA10-0AA0 with conformal coating, 0...+60 °C, Compact Switch Module CSM 1277 connection SIMATIC S7-1200 and up to 3 further nodes to Industrial Ethernet with 10/100 Mbps

| product type designation  |  |
|---|--|
| product brand name  | SIPLUS NET   |
| product type designation  | CSM 1277   |
| transfer rate   |  |
| transfer rate   | 10 Mbit/s, 100 Mbit/s  |
| ambient conditions  |  |
| ambient temperature / in horizontal mounting position / during operation  | 0 ... 60 °C  |
| installation altitude / at height above sea level / maximum   | 5000 m   |
| relative humidity   | 100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation  |
| <ul style="list-style-type: none"> <li>with condensation / according to IEC 60068-2-38 / maximum</li> </ul>   |  |
| chemical resistance / to commercially available cooling lubricants  | Yes; incl. airborne diesel and oil droplets  |
| ambient condition / relating to ambient temperature - air pressure - installation altitude  | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m) |
| resistance to biologically active substances  | Yes; Class 3B2 mold and fungal spores (excluding fauna); class 3B3 on request<br>Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)  |
| <ul style="list-style-type: none"> <li>conformity according to EN 60721-3-3</li> <li>conformity according to EN 60721-3-6</li> </ul>                        |  |
| resistance to chemically active substances  | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *<br>Yes; Class 6C3 (RH < 75%) incl. salt spray acc. to EN 60068-2-52 (Severity degree 3); *                              |
| <ul style="list-style-type: none"> <li>conformity according to EN 60721-3-3</li> <li>conformity according to EN 60721-3-6</li> </ul>                        |  |
| resistance to mechanically active substances  | Yes; Class 3S4 incl. sand, dust; *<br>Yes; Class 6S3 incl. sand, dust; *   |
| <ul style="list-style-type: none"> <li>conformity according to EN 60721-3-3</li> <li>conformity according to EN 60721-3-6</li> </ul>                        |  |
| environmental category / according to IEC 60721 / note  | * The supplied plug covers must remain in place on the unused interfaces during operation!   |
| coating / for equipped printed circuit board / according to EN 61086  | Yes; Class 2 for high availability   |
| type of coating / protection against pollution according to EN 60664-3  | Yes; protection of the type 1  |
| type of test / of the coating / according to MIL-I-46058C   | Yes; coating discoloration during service life possible  |
| product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A | Yes; conformal coating, class A  |
| protection class IP   | IP20   |
| design, dimensions and weights  |  |
| width   | 75 mm  |
| height  | 100 mm   |

|   |  |
|---|--|
| depth   | 45 mm  |
| net weight  | 0.2 kg   |
| <b>product functions / management, configuration, engineering</b> |  |
| product function  |  |
| • switch-managed  | No   |
| <b>standards, specifications, approvals</b>                       |  |
| certificate of suitability  |  |
| • CE marking  | Yes  |
| standard  |  |
| • for EMC interference emission                                   | EN 61000-6-4 (Class A)   |
| • for immunity to EMC   | EN 61000-6-2   |
| <b>product functions / general</b>                                |  |
| MTBF  | 273 a  |
| reference code  |  |
| • according to IEC 81346-2  | KF   |
| • according to IEC 81346-2:2019                                   | KFE  |
| <b>further information / internet links</b>                       |  |
| internet link   |  |
| • to website: Selection guide for cables and connectors           | <a href="https://support.industry.siemens.com/cs/ww/de/view/109766358">https://support.industry.siemens.com/cs/ww/de/view/109766358</a>  |
| • to web page: selection aid TIA Selection Tool                   | <a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a>  |
| • to website: Industrial communication                            | <a href="https://www.siemens.com/simatic-net">https://www.siemens.com/simatic-net</a>  |
| • to web page: SiePortal  | <a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a>  |
| • to website: Image database                                      | <a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a>  |
| • to website: CAX-Download-Manager                                | <a href="https://www.siemens.com/cax">https://www.siemens.com/cax</a>  |
| • to website: Industry Online Support                             | <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>  |
| <b>security information</b>                                       |  |
| security information  | Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a> . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert">https://www.siemens.com/cert</a> . (V4.7) |
| <b>Approvals / Certificates</b>                                   |  |
| <b>General Product Approval</b>                                   |  |
| <b>EMV</b>  |  |
| <a href="#">Miscellaneous</a>                                     | <br>EG-Konf.  |
| <a href="#">Manufacturer Declaration</a>                          |   |
|   | <br>UL  |
|   | <br>RCM   |
| <b>For use in hazardous locations</b>                             |  |
| <a href="#">CCC-Ex</a>  | <br>IECEX   |
|   | <br>ATEX  |
|   | <br>DNV   |
| <b>Marine / Shipping</b>  |  |

last modified:

10/23/2024 